# NSN 5930-00-258-5886

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-5886

### **Thread Class:**

2b single mounting facility

### **Overall Length:**

2.844 inches

## First Flat Length:

0.438 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.469 inches single actuator

#### **Overall Diameter:**

1.375 inches

#### Individual Section Quantity:

1

## Longest Horizontal Distance Between Mounting Centers:

1.062 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section front

### **Throw Quantity:**

3 single section front

#### **Mounting Method:**

Threaded hole single mounting facility

#### Thready Qty Per Inch (tpi):

40 single mounting facility

#### Thread Size:

0.112 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level

#### **Mounting Facility Pattern:**

Two position in-line single mounting facility

## Switch Actuator Indexing Position Quantity:

3 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section front

# NSN 5930-00-258-5886

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

### **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0