

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5945>

Hazardous Locations/environmental Protection:

Driptight and dustproof and raintight

Overall Length:

4.703 inches

Overall Height:

2.906 inches

Body Length:

4.078 inches

Unthreaded Mounting Hole Diameter:

0.297 inches

Longest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

3.125 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+240.00 actuation point pounds per square inch and +50.00/+240.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

240.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0