

View Online at <https://aerobasegroup.com/nsn/5930-00-258-5960>

Thread Class:

2b all threaded hole

Inside Diameter:

0.250 inches all connections

Overall Length:

5.656 inches

Overall Height:

4.250 inches

Overall Width:

2.031 inches

Body Height:

3.250 inches

Distance Between Mounting Facility Centers:

1.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and threaded hole

Features Provided:

Capillary tube end seal connection

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

6.5 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+425.00 actuation point pounds per square inch and +100.00/+425.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point dial and external deactuation point dial

Contact Voltage Rating In Volts:

230.0 dc at sea level third voltage

Pressure Connector Type:

Swivel nut, flare, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0