## NSN 5930-00-258-6592

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-6592

| Overall Length:   |
|---|
| 6.375 inches  |
| Overall Height:   |
| 7.750 inches  |
| Overall Width:  |
| 3.000 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.281 inches  |
| Distance Between Mounting Facility Centers:   |
| 5.250 inches  |
| Pressure Switch Type:   |
| Differential  |
| Mounting Method:  |
| Bracket and unthreaded hole   |
| Features Provided:  |
| Electrical access port  |
| Thready Qty Per Inch (tpi):   |
| 27 all pressure connection  |
| Contact Action Stimulus:  |
| Decrease  |
| Proof Pressure:   |
| 60.00 pounds per square inch  |
| Thread Size:  |
| 0.125 inches single pressure connection   |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally open, momentary action   |
| Terminal Type:  |
| Screw   |
| Contact Load Current Rating:  |
| 9.6 amperes resistive load fourth voltage   |
| Contact Adjustability:  |
| Deactuation point adjustable and actuation point adjustable                                     |
| Contact Adjustment Range:   |
| +8.00/+55.00 actuation point inches of water and +8.00/+55.00 deactuation point inches of water |
| Contact Adjustment Type:  |
| External deactuation point screw and external actuation point screw                             |
| Contact Voltage Rating In Volts:  |
| 550.0 dc at sea level third voltage   |

Pressure Connector Type:

Plain, threaded internal all connections

## **NSN 5930-00-258-6592**Pressure Switch - Page 2 of 2



| Media For Which Designed:   |
|-----------------------------|
| Gas or liquid               |
| Style Designator:           |
| Rectangular w/bracket       |
| Thread Series Designator:   |
| Npt all pressure connection |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |

Fiig: A048b0