NSN 5930-00-258-6744

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-258-6744 **Thread Class:** 2b **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.124 inches **Body Length:** 0.875 inches **Body Width:** 0.531 inches **Body Height:** 0.281 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches **Actuator Length:** 0.234 inches **Actuator Height:** 0.344 inches **Actuator Width:** 0.224 inches **Actuator Position-action Relationship:** Left position momentary **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 150.0 ac **Mounting Method:** Bracket and threaded hole Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, two positions momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive ac **Thread Series Designator:** Unc **Terminal Type And Quantity:** 3 tab, solder lug

Shelf Life:

N/a

NSN 5930-00-258-6744

Slide Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A053a0