NSN 5930-00-258-9754

Sensitive Switch - Page 1 of 2

64.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-258-9754

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
2.578 inches
Overall Height:
3.688 inches
Overall Width:
1.219 inches
Actuator Length:
1.781 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.125 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.125 inches
Housing Height:
1.312 inches
Housing Length:
2.578 inches
Housing Width:
1.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.563 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.875 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
16.0 ounces
Switch Actuating Force:

NSN 5930-00-258-9754

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.075 pretravel inches and 0.125 overtravel inches and 0.023 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0