

View Online at <https://aerobasegroup.com/nsn/5930-00-259-3360>

Thread Class:

3a single pressure connection

Overall Length:

4.938 inches

Outside Diameter:

0.375 inches single connection

Overall Height:

5.125 inches

Overall Width:

3.875 inches

Body Height:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Base

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+1.00/+15.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

13.75 deactuation point pounds per square inch gage and 1.25 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

Special Features:

Watertight case

Frequency In Hertz:

400.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Test Data Document:

81349-mils16032 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0