

View Online at <https://aerobasegroup.com/nsn/5930-00-259-3365>

Overall Length:

6.969 inches

Overall Height:

2.813 inches

Overall Width:

5.000 inches

Capillary Tube Length:

120.000 inches

Bulb Length:

3.000 inches

Bulb Diameter:

0.500 inches

End Application:

Forrestal class cv; landing craft, utility, 115 ft; nimitz class cvn; wasp class lhd; tarawa class lha; whidbey island class lsd; submarine auxillary and miscellaneous systems; I.P. Compressors; iwo jima class lph; virginia class cgn (41)

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -273.1 degrees celsius and 300.0 degrees fahrenheit

Mounting Method:

Base

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+100.00/+225.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

115.0 dc at sea level second voltage

Special Features:

Weapon system essential

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Test Data Document:

81349-mils16032 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0