# NSN 5930-00-259-3366

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-3366

Overall Length:
4.938 inches
Overall Height:
4.031 inches
Overall Width:
2.875 inches
Body Height:
2.750 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.688 inches
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
Between -273.1 degrees celsius and 300.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
4.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+150.00/+225.00 actuation point degrees fahrenheit and +150.00/+225.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
115.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage and 400.0 first voltage

Liquid

Media For Which Designed:

## NSN 5930-00-259-3366

Thermostatic Switch - Page 2 of 2



Style Designator:	Style	Design	ator:
-------------------	-------	--------	-------

Rectangular

## **Test Data Document:**

81349-mil-s-16032 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Npt single threaded bushing

## **Specification Data:**

81349-mil-s-16032 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

#### **Demilitarization:**

Yes - demil/mli

Fiig:

A048b0