NSN 5930-00-259-4734

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-4734

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
4.500 inches
Overall Height:
2.813 inches
Overall Width:
3.251 inches
Actuator Style:
Round
Actuator Free Position Height:
0.656 inches
Housing Height:
2.406 inches
Housing Length:
4.500 inches
Housing Width:
3.251 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.438 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.813 inches
Maximum Voltage Rating In Volts:
115.0 ac and 125.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Bracket and unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
80.0 inch-ounces
Switch Actuating Force:
176.0 inch-ounces
Actuator Movement:

 $5.000 \ \mbox{amperes}$ resistive dc and 20.000 amperes resistive ac

8.2 pretravel degrees and 11.5 overtravel degrees and 2.8 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

Terminal Type And Quantity:

3 screw

NSN 5930-00-259-4734

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0