## NSN 5930-00-259-5770

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-5770

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Water resistant
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.493 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
1.063 inches
Actuator Style:
Leaf
Actuator Width:
0.140 inches
Actuator Free Position Height:
0.535 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
5.0 grams
Switch Actuating Force:
30.0 grams
Actuator Movement:
Between 0.120 pretravel inches and 0.026 overtravel inches and 0.027 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
<del></del>

## NSN 5930-00-259-5770

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0