

View Online at <https://aerobasegroup.com/nsn/5930-00-259-5770>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Water resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.493 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

1.063 inches

Actuator Style:

Leaf

Actuator Width:

0.140 inches

Actuator Free Position Height:

0.535 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

5.0 grams

Switch Actuating Force:

30.0 grams

Actuator Movement:

Between 0.120 pretravel inches and 0.026 overtravel inches and 0.027 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0