NSN 5930-00-259-6820

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-6820

Body Style:
Hole mounted
Overall Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.532 inches
Overall Height:
4.375 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Actuator Style:
Round
Actuator Diameter:
0.375 inches
Actuator Height:
1.188 inches
Actuator Position-action Relationship:
Up position maintained and down position momentary and center position maintained
Actuator Position-locking Relationship:
Up position locked in and down position no locking action and center position no locking action
Maximum Voltage Rating In Volts:
230.0 ac and 230.0 dc
Inclosure Type:
Uninclosed
Thready Qty Per Inch (tpi):
48
Pile-up Contact Form Arrangement:
1c 2nd position
Thread Size:
0.099 inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 500.000 milliamperes resistive ac
Thread Series Designator:
Unc
Terminal Type And Quantity:

6 tab, solder lug

NSN 5930-00-259-6820

Lever Switch - Page 2 of 2



he		

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0