NSN 5930-00-259-6836



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-259-6836 **Body Style:** Hole mounted **Overall Length:** 3.438 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.624 inches **Overall Height:** 6.250 inches **Overall Width:** 1.313 inches **Body Length:** 3.875 inches **Body Width:** 1.313 inches **Body Height:** 1.750 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.250 inches **Actuator Style:** Round **Actuator Height:** 1.563 inches **Actuator Position-action Relationship:** Left position maintained and right position maintained **Actuator Position-locking Relationship:** Left position locked in and right position locked in **Maximum Voltage Rating In Volts:** 110.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Unthreaded hole Thready Qty Per Inch (tpi): 40 **Pile-up Contact Form Arrangement:** 6c 1st position **Thread Size:** 0.112 inches **Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive ac

Precious Material And Location:

Contacts silver

NSN 5930-00-259-6836

Lever Switch - Page 2 of 2



Thread	Series	Designator
Unc		

Terminal Type And Quantity:

30 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0