NSN 5930-00-259-6848



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-259-6848 **Body Style:** Hole mounted **Overall Length:** 2.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.625 inches **Overall Height:** 5.438 inches **Overall Width:** 1.313 inches **Body Length:** 3.375 inches **Body Width:** 1.250 inches **Body Height:** 1.750 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.250 inches **Actuator Style:** Round **Actuator Diameter:** 0.438 inches **Actuator Height:** 1.188 inches **Actuator Position-action Relationship:** Left position maintained and right position maintained **Actuator Position-locking Relationship:** Left position locked in and right position locked in **Maximum Voltage Rating In Volts:** 110.0 ac and 110.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Unthreaded hole Thready Qty Per Inch (tpi):

Pile-up Contact Form Arrangement:

4b 1st position

Thread Size:

0.112 inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 10.000 amperes resistive ac

NSN 5930-00-259-6848

Lever Switch - Page 2 of 2



Thread	Series	Designator:
--------	--------	-------------

Unc

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0