NSN 5930-00-259-6848

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-6848

Body Style:

Hole mounted

Overall Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches

Overall Height:

5.438 inches

Overall Width:

1.313 inches

Body Length:

3.375 inches

Body Width:

1.250 inches

Body Height:

1.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Actuator Style:

Round

Actuator Diameter:

0.438 inches

Actuator Height:

1.188 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Actuator Position-locking Relationship:

Left position locked in and right position locked in

Maximum Voltage Rating In Volts:

110.0 ac and 110.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

40

Pile-up Contact Form Arrangement:

4b 1st position

Thread Size:

0.112 inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 10.000 amperes resistive ac

NSN 5930-00-259-6848

Lever Switch - Page 2 of 2

Thread Series Designator:

Unc

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

