Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-7146

Hazardous Locations/environmental Protection: Dustproof **Overall Height:** 2.125 inches **Overall Width:** 1.312 inches Shaft Diameter: 0.219 inches single actuator Shaft Length: 0.234 inches single actuator **Unthreaded Mounting Hole Diameter:** 0.203 inches single mounting facility **Individual Section Quantity:** 2 Longest Horizontal Distance Between Mounting Centers: 1.969 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 2 each section front **Mounting Method:** Base single mounting facility **Contact Voltage Rating In Volts:** 120.0 dc at sea level **Switch Actuator Momentary Position:** Clockwise single actuator and counterclockwise single actuator **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator Shaft Type: Round single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Contact Load Current Rating:** 10.0 amperes resistive load dc at sea level

## **NSN 5930-00-259-7146** Rotary Switch - Page 2 of 2



## Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
1sr2b4 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0