

View Online at <https://aerobasegroup.com/nsn/5930-00-259-7154>

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

6.000 inches

Overall Width:

4.750 inches

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.562 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

5.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section front

Mounting Method:

Base single mounting facility

Contact Voltage Rating In Volts:

450.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

6sr3b4 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0