NSN 5930-00-259-7161

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-7161

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.156 inches

Shaft Diameter:

0.217 inches single actuator and 0.219 inches single actuator

Shaft Length:

0.656 inches single actuator

Overall Diameter:

4.625 inches

Individual Section Quantity:

2

Knob Manufacturer Code:

10001

Knob Manufacturer Part Number:

9s4718l alt20 piece 36

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

1 each section front

Mounting Facility Circle Radius:

0.200 inches single mounting facility

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

NSN 5930-00-259-7161

Rotary Switch - Page 2 of 2



Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0