## NSN 5930-00-259-7264

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-7264

**Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 4.657 inches First Flat Length: 0.750 inches single actuator Flat Height: 0.312 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 0.969 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 04009 **Longest Horizontal Distance Between Mounting Centers:** 2.250 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.250 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 2 each section rear **Mounting Method:** Threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 250.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 

2 single actuator

## NSN 5930-00-259-7264

Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
25.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0