## NSN 5930-00-259-7277

**Hazardous Locations/environmental Protection:** 

Rotary Switch - Page 1 of 2

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-259-7277

Dustproof
Overall Length:
7.313 inches
Overall Height:
4.750 inches
Overall Width:
4.750 inches
First Flat Length:
1.125 inches single actuator
Flat Height:
0.312 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.563 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility and 0.410 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-74095pc1
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
1 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level

## **NSN 5930-00-259-7277**Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Ferminal Type:
Threaded stud
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load dc at sea level
Style Designator:
Гар, square frame
Test Data Document:
31349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-s-15291/8 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A052b0