

View Online at <https://aerobasegroup.com/nsn/5930-00-259-7306>

Thread Class:

2b

Body Style:

Hole mount

Overall Length:

3.813 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.281 inches

Overall Height:

2.594 inches

Overall Width:

1.688 inches

Body Length:

2.313 inches

Body Width:

0.688 inches

Body Height:

1.750 inches

Actuator Style:

Rectangular

Actuator Height:

0.844 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

600.0 ac

End Application:

5ticonderoga class c (47); bath unit, portable; arleigh burke class ddg; austin ship class lpd-4 amphibious transport docks; nimitz class cvn; oliver perry class ffg; forrestal class cv; wasp class lhd; shipboard material handling equipment (mhe)

Mounting Surface To Terminal End Distance:

1.750 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Bracket and threaded hole

Nonpile-up Contact Arrangement:

3 pole, single throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0