NSN 5930-00-259-7362

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-7362

view Online at https://aerobasegroup.com/hsh/5950-00-259-7362
Hazardous Locations/environmental Protection:
Watertight
Overall Height:
14.000 inches
Overall Width:
11.375 inches
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
6
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9s5313lpc2
Longest Horizontal Distance Between Mounting Centers:
10.125 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
9.500 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
500.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw

Contact Switching Action:

Breaks before makes each section front

NSN 5930-00-259-7362

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 60.0 amperes resistive load ac at sea level Specification Or Standard: Eee3 type Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No

Fiig:

A052b0