

View Online at <https://aerobasegroup.com/nsn/5930-00-259-7363>

Hazardous Locations/environmental Protection:

Watertight

Overall Height:

12.500 inches

Overall Width:

14.312 inches

First Flat Length:

0.875 inches single actuator

Flat Height:

0.446 inches single actuator and 0.448 inches single actuator

Shaft Diameter:

0.624 inches single actuator and 0.625 inches single actuator

Unthreaded Mounting Hole Diameter:

0.531 inches single mounting facility

Individual Section Quantity:

4

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9s5360lpc6

Longest Horizontal Distance Between Mounting Centers:

13.062 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

8.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

2 each section front

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0