NSN 5930-00-259-7367

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-7367

Hazardous Locations/environmental Protection:

Dustproof

Shaft Length:

1.094 inches single actuator

Overall Diameter:

3.750 inches

Unthreaded Mounting Hole Diameter:

0.190 inches single mounting facility

Individual Section Quantity:

10

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6202-73075-1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section front

Mounting Facility Circle Radius:

1.625 inches single mounting facility

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

NSN 5930-00-259-7367

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

S3jr10 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0