NSN 5930-00-259-7368

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-7368

Hazardous Locations/environmental Protection:

Watertight

Shaft Diameter:

0.218 inches single actuator

Unthreaded Mounting Hole Diameter:

0.219 inches single mounting facility

Individual Section Quantity:

2

Knob Manufacturer Code:

10001

Knob Manufacturer Part Number:

9000-s6202-74000-1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section front

Throw Quantity:

1 each section rear

Mounting Facility Circle Radius:

5.625 inches single mounting facility

Mounting Method:

Base single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

NSN 5930-00-259-7368

Rotary Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0