NSN 5930-00-259-7879

Rotary Switch - Page 1 of 2

Thread Class:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-259-7879

Thread Length: 0.250 inches single mounting facility **Overall Length:** 1.250 inches **Overall Height:** 1.531 inches **Overall Width:** 1.375 inches First Flat Length: 0.312 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.625 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 4 single section front **Throw Quantity:** 5 single section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks, breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator

NSN 5930-00-259-7879

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level **Special Features:** 2 dummy terminals on front of section one **Precious Material And Location:** Contacts and rotor blade surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A052b0