

View Online at <https://aerobasegroup.com/nsn/5930-00-259-7982>

Overall Length:

4.500 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.563 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.080 inches and 1.084 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.540 inches and 0.542 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.935 inches and 0.939 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 650.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

176.00 actuation point degrees fahrenheit and 164.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0