# NSN 5930-00-259-8073

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8073

## **Thread Class:**

2b single mounting facility

#### **Overall Length:**

2.875 inches

## Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.000 inches single actuator

## **Overall Diameter:**

1.750 inches

## Individual Section Quantity:

1

## Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

3 single section front

#### **Throw Quantity:**

4 single section front

## Mounting Method:

Threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.138 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Mounting Facility Pattern:

Two position in-line single mounting facility

#### Switch Actuator Indexing Position Quantity:

4 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section front

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-259-8073

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

150.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0