

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8225>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.872 inches and 0.878 inches

**Body Length:**

Between 1.079 inches and 1.109 inches

**Body Width:**

Between 0.385 inches and 0.415 inches

**Body Height:**

Between 0.610 inches and 0.650 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.116 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.875 inches

**Actuator Length:**

Between 0.105 inches and 0.115 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

Between 0.160 inches and 0.170 inches

**Actuator Free Position Height:**

0.625 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 6.0 ounces and 14.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.006 differential inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0