

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8262>

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

7.500 inches

Overall Width:

5.500 inches

First Flat Length:

0.625 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.062 inches single actuator

Unthreaded Mounting Hole Diameter:

0.408 inches single mounting facility

Individual Section Quantity:

6

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6202-74095pc1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section front

Mounting Facility Circle Radius:

1.890 inches single mounting facility

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

450.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

6sr3e1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0