

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8264>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.438 inches

**Overall Height:**

2.875 inches

**Overall Width:**

4.125 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.312 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Individual Section Quantity:**

3

**Knob Manufacturer Code:**

80064

**Knob Manufacturer Part Number:**

9000s6202-74089pc3

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

3 single section rear

**Mounting Facility Circle Radius:**

1.609 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

450.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Shaft Flat/slot Angular Location:**

90.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single mounting facility

**Specification Or Standard:**

3sr class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0