

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8273>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.125 inches

Overall Height:

4.375 inches

Overall Width:

4.125 inches

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.562 inches single actuator

Unthreaded Mounting Hole Diameter:

0.312 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

3.812 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section in-line

Throw Quantity:

2 each section in-line

Mounting Method:

Bracket single mounting facility

Contact Voltage Rating In Volts:

450.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

3sr class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0