

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8273>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.125 inches

**Overall Height:**

4.375 inches

**Overall Width:**

4.125 inches

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

0.562 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.312 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

3.812 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section in-line

**Throw Quantity:**

2 each section in-line

**Mounting Method:**

Bracket single mounting facility

**Contact Voltage Rating In Volts:**

450.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

3sr class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0