## NSN 5930-00-259-8616

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-259-8616

Maximum Voltage Rating In Volts: 460.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A053a0	Actuator Free Position Height:
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.140 inches
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action single switch unit Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Maximum Voltage Rating In Volts:
Fully enclosed  Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action single switch unit  Switch Release Force:  0.5 ounces  Switch Actuating Force:  6.0 ounces  Actuator Movement:  Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	460.0 ac
Nonpile-up Contact Arrangement:  1 pole, single throw, normally closed, momentary action single switch unit  Switch Release Force:  0.5 ounces  Switch Actuating Force: 6.0 ounces  Actuator Movement:  Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Inclosure Type:
1 pole, single throw, normally closed, momentary action single switch unit  Switch Release Force: 0.5 ounces  Switch Actuating Force: 6.0 ounces  Actuator Movement:  Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Fully enclosed
Switch Release Force: 0.5 ounces Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Nonpile-up Contact Arrangement:
Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1 pole, single throw, normally closed, momentary action single switch unit
Switch Actuating Force: 6.0 ounces Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Switch Release Force:
Actuator Movement: Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.5 ounces
Actuator Movement:  Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Switch Actuating Force:
Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 3.000 amperes resistive ac  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	6.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:  3.000 amperes resistive ac  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Actuator Movement:
3.000 amperes resistive ac  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches
Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Contact Load Current Rating At Maximum Rated Voltage:
2 tab, solder lug  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.000 amperes resistive ac
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 tab, solder lug
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
•	No
A053a0	Fiig:
	A053a0