## NSN 5930-00-259-8676

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8676

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
15.750 inches
Overall Height:
5.250 inches
Overall Width:
5.250 inches
Body Diameter:
0.750 inches
Body Length:
10.000 inches
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
1000.0 degrees fahrenheit
Mounting Method:
Immersion well
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
4.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+675.00/+925.00 actuation point degrees fahrenheit and +675.00/+925.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
Internal deactuation point screw and internal actuation point screw
Contact Voltage Rating In Volts:
115.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Test Data Decument:

81349-mil-s-16032 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5930-00-259-8676

Thermostatic Switch - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0