

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8810>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Actuator Length:**

2.500 inches

**Actuator Style:**

Roller arm

**Actuator Height:**

1.000 inches

**Actuator Roller Diameter:**

1.000 inches

**Actuator Roller Width:**

0.250 inches

**Housing Height:**

3.062 inches

**Housing Length:**

6.125 inches

**Housing Width:**

3.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

5.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

2.375 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

Between 36.0 pretravel degrees and 45.0 pretravel degrees and 15.0 overtravel degrees and 5.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

0.500 amperes resistive dc and 1.500 amperes resistive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0