NSN 5930-00-259-8882

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8882

Hazardous	Locations	lanviranm	ontal [Protoction:
mazardous	Locations	/environiii	entai i	rotection:

Watertight

Overall Diameter:

6.375 inches

Unthreaded Mounting Hole Diameter:

0.375 inches single mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6504-74055pc2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

2 each section front

Mounting Facility Circle Radius:

2.812 inches single mounting facility

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.252 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-00-259-8882

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

10.0 amperes resistive load ac at sea level

Specification Or Standard:

S2jr-3-22 type

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A052b0