# NSN 5930-00-259-8882



Rotary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-259-8882
Hazardous Locations/environmental Protection:
Watertight
Overall Diameter:
6.375 inches
Unthreaded Mounting Hole Diameter:
0.375 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6504-74055pc2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Mounting Facility Circle Radius:
2.812 inches single mounting facility
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
125.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Three position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.252 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 de sus estado estudor

45.0 degrees single actuator

## NSN 5930-00-259-8882

Rotary Switch - Page 2 of 2



#### **Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

#### Specification Or Standard:

S2jr-3-22 type

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A052b0