

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8883>

Hazardous Locations/environmental Protection:

Watertight

Overall Diameter:

6.375 inches

Unthreaded Mounting Hole Diameter:

0.375 inches single mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6504-74055pc1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

2 each section front

Mounting Facility Circle Radius:

1.406 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.252 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Specification Or Standard:

S2jr-3-22I type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0