## NSN 5930-00-259-8885

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8885

## **Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Overall Diameter:** 

6.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.375 inches single mounting facility

**Individual Section Quantity:** 

3

**Knob Manufacturer Code:** 

80064

**Knob Manufacturer Part Number:** 

9000s6504-74055pc69

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section front

**Throw Quantity:** 

3 each section front

**Mounting Facility Circle Radius:** 

1.406 inches single mounting facility

**Mounting Method:** 

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:** 

Actuator knob and metallic inclosure

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Switch Actuator Momentary Position:** 

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:** 

Three position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Rectangular/square, threaded hole single actuator

**Square Shaft Size:** 

0.252 inches single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## NSN 5930-00-259-8885

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, circular, bushing mount

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0