## NSN 5930-00-259-8888

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8888
Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Shaft Length:
1.500 inches single actuator
Unthreaded Mounting Hole Diameter:
0.266 inches single mounting facility
Individual Section Quantity:
3
Longest Horizontal Distance Between Mounting Centers:
2.312 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.312 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Contact Voltage Rating In Volts:
125.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Specification Or Standard:

Jr304 type

## NSN 5930-00-259-8888

Rotary Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0