NSN 5930-00-259-8889

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-259-8889 | | |
|--|--|--|
| Hazardous Locations/environmental Protection: | | |
| Dustproof | | |
| Overall Height: | | |
| 2.812 inches | | |
| Overall Width: | | |
| 2.812 inches | | |
| Shaft Length: | | |
| 1.500 inches single actuator | | |
| Unthreaded Mounting Hole Diameter: | | |
| 0.266 inches single mounting facility | | |
| Individual Section Quantity: | | |
| 3 | | |
| Longest Horizontal Distance Between Mounting Centers: | | |
| 2.312 inches single mounting facility | | |
| Longest Vertical Distance Between Mounting Centers: | | |
| 2.312 inches single mounting facility | | |
| End Application: | | |
| Ship ohio class ssn trident | | |
| Switch Contact Basic Design: | | |
| Nonpile-up symmetrical | | |
| Pole Quantity: | | |
| 2 each section front | | |
| Throw Quantity: | | |
| 2 each section front | | |
| Contact Voltage Rating In Volts: | | |
| 125.0 ac at sea level | | |
| Switch Actuator Momentary Position: | | |
| Clockwise single actuator and counterclockwise single actuator | | |
| Mounting Facility Pattern: | | |
| Four position rectangular single mounting facility | | |
| Switch Actuator Indexing Position Quantity: | | |
| 2 single actuator | | |
| Shaft Type: | | |
| Rectangular/square, threaded hole single actuator | | |
| Terminal Type: | | |
| Tab w/screw | | |
| Contact Switching Action: | | |
| Breaks before makes each section front | | |
| Switch Actuator Positioning Increment: | | |
| 45.0 degrees single actuator | | |

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

NSN 5930-00-259-8889

Rotary Switch - Page 2 of 2



| Specification | Or Standard: |
|---------------|--------------|
|---------------|--------------|

Jr-300 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0