# NSN 5930-00-259-8894

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8894

## **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

10.906 inches

## **Overall Height:**

2.812 inches

## **Overall Width:**

2.812 inches

### Shaft Length:

1.344 inches single actuator

### Individual Section Quantity:

20

### Knob Manufacturer Code:

80064

### Knob Manufacturer Part Number:

9000-s6202-73075-1

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section front

#### Throw Quantity:

8 each section front

## Mounting Facility Circle Radius:

1.625 inches single mounting facility

## **Mounting Method:**

Bracket single mounting facility

## **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

24 single mounting facility

#### **Thread Size:**

0.190 inches single mounting facility

## Contact Voltage Rating In Volts:

125.0 ac at sea level

## Shaft Flat/slot Angular Location:

22.5 degrees from contact position 1 single actuator

## Mounting Facility Pattern:

Four position circular single mounting facility

## Switch Actuator Indexing Position Quantity:

8 single actuator

# NSN 5930-00-259-8894

Rotary Switch - Page 2 of 2



### Shaft Type:

Rectangular/square, threaded hole single actuator

### Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

### **Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

#### **Style Designator:**

Tap, square frame

#### **Test Data Document:**

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator: Unc single mounting facility

## **Specification Data:**

81349-mil-s-21604/5 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0