## NSN 5930-00-259-8903

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8903
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:

Watertight

**Overall Length:** 

14.616 inches

**Overall Height:** 

8.000 inches

**Overall Width:** 

8.000 inches

First Flat Length:

0.866 inches single actuator

**Shaft Diameter:** 

0.625 inches single actuator

**Shaft Length:** 

1.304 inches single actuator

**Individual Section Quantity:** 

15

**Knob Manufacturer Code:** 

80064

**Knob Manufacturer Part Number:** 

9-s-5564-I-19

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

2 each section front

**Throw Quantity:** 

8 each section front

**Mounting Facility Circle Radius:** 

7.000 inches single mounting facility

**Mounting Method:** 

Bracket single mounting facility

**Features Provided:** 

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Shaft Flat/slot Angular Location:** 

22.5 degrees from contact position 1 single actuator

## **NSN 5930-00-259-8903**Rotary Switch - Page 2 of 2



Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, square single actuator
Square Shaft Size:
0.375 inches single actuator
Ferminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Special Features:
6-32 threaded hole located on vertical axis of shaft
Style Designator:
Гар, circuit selector
Test Data Document:
30064-9-s-5568-I drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No No
Filg:
A052b0