NSN 5930-00-259-8951

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-8951

Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
3.750 inches
Overall Width:
2.188 inches
First Flat Length:
0.438 inches single actuator
Flat Height:
0.217 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.812 inches single actuator
Individual Section Quantity:
4
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-74000pc2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section front
Mounting Facility Circle Radius:
2.312 inches single mounting facility
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
120.0 dc at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
-

Shaft Type:

Round, flatted single actuator

NSN 5930-00-259-8951

Rotary Switch - Page 2 of 2

A052b0



Terminal Type:
Threaded stud
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Test Data Document:
81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
1sr class
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fila: