

View Online at <https://aerobasegroup.com/nsn/5930-00-259-8957>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Height:**

3.750 inches

**Overall Width:**

2.188 inches

**First Flat Length:**

0.438 inches single actuator

**Flat Height:**

0.217 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.812 inches single actuator

**Individual Section Quantity:**

6

**Knob Manufacturer Code:**

80064

**Knob Manufacturer Part Number:**

9000s6202-74000pc2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

2 each section front

**Mounting Facility Circle Radius:**

2.312 inches single mounting facility

**Mounting Method:**

Base single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

120.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Threaded stud

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

**Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

1sr6f1 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0