NSN 5930-00-259-8958

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Dustproof



View Online at https://aerobasegroup.com/nsn/5930-00-259-8958

Overall Height:
2.125 inches
Overall Width:
1.562 inches
Shaft Diameter:
0.218 inches single actuator
Shaft Length:
1.438 inches single actuator
Unthreaded Mounting Hole Diameter:
0.203 inches single mounting facility
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
1.969 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Base single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
120.0 dc at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:

Test Data Document:

10.0 amperes resistive load ac at sea level

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-00-259-8958

Rotary Switch - Page 2 of 2



Specification Or Stand	

1sr class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0