

View Online at <https://aerobasegroup.com/nsn/5930-00-259-9477>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Explosion proof

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.906 inches

Actuator Roller Diameter:

1.000 inches

Actuator Roller Width:

0.250 inches

Housing Height:

3.062 inches

Housing Length:

6.125 inches

Housing Width:

3.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.375 inches

Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Actuator Movement:

Between 0.310 pretravel inches and 0.158 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes inductive dc and 1.500 amperes inductive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0