# NSN 5930-00-259-9550

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-259-9550

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

2.281 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

1.188 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.625 inches single actuator

## Individual Section Quantity:

1

#### Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 single section rear

## **Throw Quantity:**

1 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Features Provided:**

Metallic inclosure

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.344 inches single mounting facility

## Contact Voltage Rating In Volts:

250.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

2 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

# NSN 5930-00-259-9550

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

50.0 degrees single actuator

#### **Contact Load Current Rating:**

3.0 amperes resistive load ac at sea level

Style Designator:

Rectangular panel mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0